- WHITE

	Pack (number of units)	
	Volume (dm³)	2,2
	Weight (g)	493
Product characteristics		General characteristics
at. 6A RJ 45 sockets		Mosaic [™] Programme mechanisms - RJ 45 sockets - cat. 6A
TP - 2 modules		and 6
 360° metal shielding 		Can be integrated in all supports Contacts marked with dual colour code and wiring schemes T 568 A
• White		and T 568 B
		Conform to standards ISO/IEC 11801 Ed. 3.0, amendment 2, EN
		50173-1 and TIA/EIA C
Documentation		
ocumentation		
Catalogue pages & additional information	n	Installation instructions & related documents
<u>Selection chart (p.720)</u>		• <u>LE01557AJ</u>
 Description page (p.732) 		
 <u>Selection chart (p.830-831)</u> 		
 Description page (p.891) 		
-		
Installation & technical data		Agreements & certificates of conformity
- <u>F00950EN-08</u>		 AoC-PL2 Cat6A FFTP 32799 ac1171009
		• <u>AoC-CL2 Cat6A FFTP 32799 ac1171010</u>
		• AoC-PL2 Cat6A FTP 32778 ac1171014
		 <u>AoC-CL2 Cat6A STP 32777 ac1171018A</u> <u>AoC-PL3 Cat6A FTP 32778 ac1171016</u>
		AOC-CL2 Cat6A FTP 32778 ac1171010
		• AoC-PL3 Cat6A STP 32777 ac1171019A
		 AoC-PL2 Cat6A STP 32777 ac1171017A
		• AoC-CL4 Cat6A STP 32869 ac1181045
		 AoC-CL4 Cat6A STP 32778 ac1181044
		 AoC-PL2 C6A FFTP 32883 ac1191060
		 AoC-CL2 C6A FFTP 32883 ac1191061
		 <u>AoC-PL2 C6A UFTP 32884 ac1191058</u>
		• AOC-CL2 C6A STP 32882 ac1191063
		<u>AoC-4PPoE 2019-676 Ac Delta Force</u> AoC CL2 CCA LIETE 22884 ac11010F0
		 <u>AoC-CL2 C6A UFTP 32884 ac1191059</u> AoC-PL3 Cat6A FFTP 32799 ac1171011
		 AoC-PL2 C6A STP 32882 ac1191062

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018 The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.