

# PHILIPS

# Lighting



## SmartBright Road

BRP130 LED88/NW 70W 220-240V DM GM

SmartBright Road, 8800 lm, 70 W, Neutral white, Safety class I

The SmartBright road is ideal for new streets and for renovating existing installations, this affordable range of lighting solutions combines clean, high-quality light with significant energy savings and reduced maintenance.

### Product data

General Information		Cable	
Driver included	Yes	Cable	Cable 0.5 m without plug
CE mark	CE mark	Temperature	
Flammability mark	For mounting on normally flammable surfaces	Ambient temperature range	-40 to +50 °C
Light Technical		Controls and Dimming	
Luminous Flux	8,800 lm	Dimmable	No
Correlated Color Temperature (Nom)	4000 K	Control interface	-
Luminous Efficacy (rated) (Nom)	130 lm/W	Mechanical and Housing	
Color rendering index (CRI)	>70	Housing Material	Aluminum
Light source color	Neutral white	Optical cover material	Polycarbonate
Optical cover type	Transparent bowl with transparent cover	Housing Color	Gray
Operating and Electrical		Overall length	383 mm
Input Voltage	220-240 V	Overall width	249 mm
Line Frequency	50 or 60 Hz	Overall height	85 mm
Inrush current	15 A	Effective projected area	0.08 m <sup>2</sup>
Power Consumption	70 W	Dimensions (Height x Width x Depth)	85 x 249 x 383 mm

Power Factor (Fraction)	0.9
Connection	Screw connection block 3-pole

## Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
-------------------------	--

Datasheet, 2023, December 14

data subject to change

Mech. impact protection code	IK08 [5 J vandal-protected]	Full product name	BRP130 LED88/NW 70W 220-240V DM GM
Protection class IEC	Safety class I	Full product code	871951454888600
		Order code	911401676007
		Material Nr. (12NC)	911401676007
		Numerator - Quantity Per Pack	1
		EAN/UPC - Product/Case	8719514548886
		Numerator - Packs per outer box	1
		EAN/UPC - Case	8719514548886

## SmartBright Road


### Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	7
Power consumption tolerance	+/-10%

### Dimensional drawing

### Product Data

Order product name BRP130 LED88/NW 70W 220-240V DM GM



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, December 14 - data subject to change