



# Lighting

## **SmartBright Road**

### BRP132 LED175/CW 140W 220-240V DM GM

SmartBright Road, 17500 lm, 140 W, Cool white, Safety class I

The SmartBright road is ideal for new streets and for renovating existing installations, this affordable range of lighting solutions combines clean, high-quality light with significant energy savings and reduced maintenance.

#### **Product data**

eneral Information		Cable	Cable 0.5 m without plug
river included	Yes	_	
E mark	CE mark	Temperature	
lammability mark	For mounting on normally flammable surfaces		
		Ambient temperature range	-40 to +50 °C
		_	
ight Technical			
		Controls and Dimming	
uminous Flux	17,500 lm		
orrelated Color Temperature (Nom)	5700 К	Dimmable	No
uminous Efficacy (rated) (Nom)	130 lm/W	Control interface	-
Color rendering index (CRI)	>70		
ight source color	Cool white	Mechanical and Housing	
Optical cover type	Transparent bowl with transparent cover		
		Housing Material	Aluminum
		Optical cover material	Polycarbonate

#### **Operating and Electrical**

Input Voltage	220-240 V
Line Frequency	50 or 60 Hz
Inrush current	15 A
Power Consumption	140 W

Housing Material	Aluminum	
Optical cover material	Polycarbonate	
Housing Color	Gray	
Overall length	509 mm	
Overall width	326 mm	
Overall height	85 mm	
Effective projected area	0.14 m <sup>2</sup>	
Dimensions (Height x Width x Depth)	85 x 326 x 509 mm	

ower Factor (Fraction)	0.9		
Connection	Screw connection block 3-pole		
		Approval and Application	
		Ingress protection code	IP66 [Dust penetration-protected, jet-proof]

#### Datasheet, 2023, December 14

Datasheet, 2023, December 14			data subject to change
Mech. impact protection code	IK08 [5 J vandal-protected]	Full product name	BRP132 LED175/CW 140W 220-240V DM GM
Protection class IEC	Safety class I	Full product code	871951454895400
		Order code	911401676707
		Material Nr. (12NC)	911401676707
SmartBright Road		Numerator - Quantity Per Pack	1
		EAN/UPC - Product/Case	8719514548954
		Numerator - Packs per outer box	1
Initial Performance (IEC Compliant)		 EAN/UPC - Case	8719514548954
Luminous flux tolerance	+/-10%		0720010.0001
Initial chromaticity	7	Dimensional	
Power consumption tolerance	+/-10%	-drawing	

#### Product Data

Order product name

BRP132 LED175/CW 140W 220-240V DM GM



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are

www.lighting.philips.com 2023, December 14 - data subject to change

registered trademarks of Koninklijke Philips N.V.