



# RoadFlair Gen2

## BRP491 LED142/NW 100W 220-240V DM GM

RoadFlair Gen2, 14200 lm, 100 W, 740 neutral white, Analog, Safety class I

RoadFlair Gen2 is brand new design road lighting product family, set to meet customers' all-round requirements, including high lumen efficacy for energy saving and sustainability, aesthetic design for nice shape and appearance, quality material and components for product reliability and long lifetime, professional optics for various applications fulfillment, dimming and system control interface for improving municipal operations and offering future-proof features. RoadFlair Gen2 competitive price would help on the acceleration of road lighting LED transformation, to a more sustainable society and smarter city.

#### **Product data**

General Information		Power Consumption	100 W
		Power Factor (Fraction)	0.95
Driver included	Yes	Connection	Screw connection block 3-pole
CE mark	CE mark	Cable	-
Light Technical		Temperature	
Luminous Flux	14,200 lm	Ambient temperature range	-40 to +50 °C
Correlated Color Temperature (Nom)	4000 K	·	
Luminous Efficacy (rated) (Nom)	140 lm/W		
Color rendering index (CRI)	>70	Controls and Dimming	
Light source color	740 neutral white		
Optical cover type	Polycarbonate micro lens optic	Dimmable	Yes
		Control interface	Analog
Operating and Electrical			
· ·		Mechanical and Housing	
Input Voltage	220 to 240 V		
Line Frequency	50 or 60 Hz	Housing Material	Aluminium pressure die cast

Datasheet, 2023, December 13 data subject to change


### RoadFlair Gen2

Housing Color	Aluminum and gray			
Overall length	355 mm			
Overall width	230 mm			
Overall height	136 mm			
Dimensions (Height x Width x Depth)	136 x 230 x 355 mm			
Approval and Application				
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]			
Mech. impact protection code	IK08 [5 J vandal-protected]			
Protection class IEC	Safety class I			

Product Data			
Order product name	BRP491 LED142/NW 100W 220-240V DM GM		
Full product name	BRP491 LED142/NW 100W 220-240V DM GM		
Full product code	872016972837000		
Order code	911401673306		
Material Nr. (12NC)	911401673306		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	8720169728370		
Numerator - Packs per outer box	1		
EAN/UPC - Case	8720169728370		

Initial Performance (IEC Compliant)				
Luminous flux tolerance	+/-10%			
Power consumption tolerance	+/-10%			

## **Dimensional drawing**



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, December 13 - data subject to change