

Product datasheet

Specifications



Circuit breaker, ComPacT NSX160H, 70kA/415VAC, 4 poles 3D (neutral not protected), TMD trip unit 160A

C16H6TM160

Main

Range	ComPacT new generation
Product name	ComPacT NSX new generation
Device short name	NSX160H
Product or component type	Circuit breaker
Device application	Distribution
Poles description	4P
Protected poles description	3D
Neutral position	Left
[In] rated current	160 A at 40 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network frequency	50/60 Hz
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Utilisation category	Category A
[Icu] rated ultimate short-circuit breaking capacity	100 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 70 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 65 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 50 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 35 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 10 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2
Performance level	H 70 kA 415 V AC
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Trip unit protection functions	LI
[Ics] rated service short-circuit breaking capacity	100 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 70 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2

Control type	Toggle
---------------------	--------

Circuit breaker mounting mode	Fixed
--------------------------------------	-------

Complementary

[Ui] rated insulation voltage	800 V AC 50/60 Hz
--------------------------------------	-------------------

[Uimp] rated impulse withstand voltage	8 kV
---	------

65 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2
50 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2
35 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2
10 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2

Mechanical durability	40000 cycles
------------------------------	--------------

Electrical durability	40000 cycles at 440 V In/2 20000 cycles at 440 V In 15000 cycles at 690 V In/2 7500 cycles at 690 V In
------------------------------	---

Power dissipation per pole	13.95 W
-----------------------------------	---------

Mounting support	Backplate
-------------------------	-----------

Mounting position	Horizontal and vertical Flat on the back
--------------------------	---

Upside connection	Front
--------------------------	-------

Downside connection	Front
----------------------------	-------

Connection pitch	35 mm
-------------------------	-------

Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
------------------------	--

Trip unit rating	160 A at 40 °C
-------------------------	----------------

Long-time pick-up adjustment type Ir (thermal protection)	Adjustable
--	------------

[Ir] long-time protection pick-up adjustment range	0.7...1 x In
---	--------------

Long-time protection delay adjustment type tr	Fixed
--	-------

[Tr] long-time protection delay adjustment range	120...400 s at 1.5 x In 15 s at 6 x Ir
---	---

Neutral protection settings	No protection (3D)
------------------------------------	--------------------

Instantaneous protection pickup adjustment type Ii	Fixed
---	-------

[Ii] instantaneous protection pick-up adjustment range	1250 A
---	--------

Earth-leakage protection	Without
---------------------------------	---------

Number of slots for electrical auxiliaries	5 slot(s)
---	-----------

Width (W)	140 mm
------------------	--------

Height (H)	161 mm
-------------------	--------

Depth (D)	86 mm
------------------	-------

Product weight	2.6 kg
Environment	
Standards	EN/IEC 60947
Product certifications	CCC EAC Marine
Overvoltage category	Class II
Electrical shock protection class	Class II
Pollution degree	3 conforming to IEC 60664-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Ambient air temperature for operation	-25...70 °C

Ambient air temperature for storage	-50...85 °C
Relative humidity	0...95 %
Operating altitude	0...2000 m without derating 2000 m...5000 m with derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.0 cm
Package 1 Width	14.5 cm
Package 1 Length	19.0 cm
Package 1 Weight	2.376 kg
Unit Type of Package 2	S03
Number of Units in Package 2	4
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	9.888 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes

China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes

