

# PHILIPS

## Lighting



# Essential SmartBright G3 LED Floodlight

## BVP150 LED42/CW 220-240V 50W SWB CE

Essential SmartBright G3 LED Floodlight - 4250 lm - 50 W - 6500 K

The Essential SmartBright G3 LED floodlight comes with a compact and sturdy design. Its light weight with robust die-cast aluminum housing and corrosion-proof coating, suitable for general outdoor application. Higher efficacy than last generation, achieves more energy savings.

### Product data

General Information		Serviceability class	
Light source color	865 cool daylight	Class C, luminaire without serviceable parts, not serviceable	
Light source replaceable	No	Light Technical	
Driver included	Yes	Standard tilt angle posttop	-
Optical cover/lens type	Glass bowl/cover	Standard tilt angle side entry	-
Luminaire light beam spread	110°	Operating and Electrical	
Control interface	-	Input Voltage	220 to 240 V
Connection	Flying leads/wires	Input Frequency	50 to 60 Hz
Cable	Cable 0.3 m without plug	Inrush current	1.11 A
Protection class IEC	Safety class I	Inrush time	0.0132 ms
Flammability mark	For mounting on normally flammable surfaces	Power Factor (Min)	0.9
CE mark	CE mark	Controls and Dimming	
Optic type outdoor	Symmetrical wide beam	Dimmable	No
Constant light output	No		
Number of products on MCB of 16 A type B 44			
Light source engine type	LED		

# Essential SmartBright G3 LED Floodlight

## Mechanical and Housing

Housing Material	Aluminum die cast
Optical cover/lens material	Glass
Fixation material	Steel
Mounting device	Mounting bracket adjustable
Optical cover/lens shape	Flat
Optical cover/lens finish	Textured
Overall length	200 mm
Overall width	145 mm
Overall height	33 mm
Color	Black

## Approval and Application

Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [ 1 J]
Surge Protection (Common/Differential)	Surge protection level until 2 kV

## Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	4250 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	85 lm/W

Init. Corr. Color Temperature	6500 K
Init. Color Rendering Index	>80
Initial chromaticity	SDCM<7
Initial input power	50 W
Power consumption tolerance	+/-10%

## Application Conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

## Product Data

Full product code	871016333022899
Order product name	BVP150 LED42/CW 220-240V 50W SWB CE
EAN/UPC - Product	8710163330228
Order code	911401732432
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8
Material Nr. (12NC)	911401732432
Net Weight (Piece)	0.650 kg



## Dimensional drawing



BVP150 LED42/CW 220-240V 50W SWB CE

