



SmartBright LED Floodlight

BVP176 LED190/CW 200W WB GREY CE

SmartBright LED Floodlight - 19000 lm - 200 W - 5700 K

The SmartBright LED Floodlight is a versatile floodlight engineered to deliver significant energy savings, an ideal solution for diverse floodlighting applications. The product is also designed to meet relevant performance and safety standards, offering you reliable and long-lasting performance.

Product data

General Information	
Lamp family code	LED190 [LED module 19000 lm]
Light source color	757 cool white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	Polycarbonate bowl/cover UV-resistant
Luminaire light beam spread	30° x 80°
Control interface	.iso
Connection	Flying leads/wires
Cable	Cable 0.6 m without plug
Protection class IEC	Safety class I
Flammability mark	For mounting on normally flammable
	surfaces
CE mark	CE mark
ENEC mark	8 4 8
Constant light output	No
Number of products on MCB of 16 A	type B 13

Light source engine type	LED
Operating and Electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Inrush current	11.5 A
Inrush time	0.077 ms
Power Factor (Min)	0.9
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing Material	Aluminum die cast
Optical cover/lens material	Polycarbonate
Mounting device	Mounting bracket adjustable
Optical cover/lens shape	Flat
Optical cover/lens finish	Frosted

Datasheet, 2021, November 8 data subject to change


SmartBright LED Floodlight


Overall length	390 mm
Overall width	287 mm
Overall height	62 mm
Effective projected area	0.1365 m²
Color	Gray
Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-
	proof]
Mech. impact protection code	IK07 [2 J reinforced]
Initial Performance (IEC Complian	nt)
Initial luminous flux (system flux)	19000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	95 lm/W
Init. Corr. Color Temperature	5700 K
Init. Color Rendering Index	>70
Initial chromaticity	SDCM<7

Initial input power	200 W
Power consumption tolerance	+/-10%
Application Conditions	
Ambient temperature range	-40 to +45 °C
Product Data	
Full product code	871016331968199
Order product name	BVP176 LED190/CW 200W WB GREY CE
EAN/UPC - Product	8710163319681
Order code	911401629604
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	3
Material Nr. (12NC)	911401629604
Net Weight (Piece)	4.400 kg



Dimensional drawing







© 2021 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered

2021, November 8 - data subject to change