

PHILIPS

Lighting

SmartBright Direct Panel G2

RC048B LED38S/865 PSU W30L120 GM

- Acrylate

The new Philips Smartbright Direct panel offers exceptional value. It is Perfect for your everyday ceiling lighting installations. It is available in 2 standard sizes and 2 different CCT options to suit your need.

Product data

General Information

Light source engine type LED

Light Technical

Luminous Flux 3,800 lumen

Correlated Color Temperature (Nom) 6500 K

Luminous Efficacy (rated) (Nom) 95 lm/W

Color rendering index (CRI) >80

Light source color 865 cool daylight

Optical cover/lens type Acrylate

Operating and Electrical

Input Voltage 220 to 240 V

Line Frequency 50 or 60 Hz

Input Frequency 50 or 60 Hz

Power Consumption 40 W

Inrush current 25 A

Power Factor (Fraction) 0.9

Number of products on MCB of 16 A type B 10

Temperature

Ambient temperature range -10 to +35 °C

Controls and Dimming

Dimmable No

Control interface -

Mechanical and Housing

Housing Material Steel

Optical cover/lens material Polystyrene

Housing Color White RAL 9003

Optical cover/lens finish Opal

Overall length 1,195 mm

Overall width 295 mm

Overall height 34 mm

Effective projected area 0.353 m²

SmartBright Direct Panel G2

Dimensions (Height x Width x Depth)	34 x 295 x 1195 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class II
Flammability mark	For mounting on normally flammable surfaces
CE mark	-

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.31, 0.33) SDCM≤5
Power consumption tolerance	+/-10%

Product Data	
Full product code	871951452821599
Order product name	RC048B LED38S/865 PSU W30L120 GM
Order code	911401845482
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material number (12NC)	911401845482
Full product name	RC048B LED38S/865 PSU W30L120 GM
EAN/UPC - Case	8719514528215



Dimensional drawing

