





MONOBLOC MODULAR DISTRIBUTION BLOCK - 4P - 160 A - 15 CONNECTIONS

Pack (number of units)	1
Volume (dm ³)	1,619
Weight (g)	715,00

Product characteristics

Monobloc modular distribution blocks

- Mounting on rail or on plate with 2 screws
- Supplied with insulated back plate and transparent protective front cover
- Each bar can be labelled using CAB 3
- Possible to add IP 2X terminal block

Four pole

- Equipped with 4 bars
- With short ferrule supplied for flexible connection 25 mm²
- Rating : 160 A
- Isc peak : 27 kA
- Icw : 8.4 kA
- Number of modules : 10

General characteristics

Modular distribution blocks 40 to 250 A

- Standard distribution
- Connection with or without Starfix ferrules
- Self-extinguishing, according to EN 60695-2-11: 960 °C on active part supports

Documentation



Catalogue pages & additional information

- [Selection chart \(p.198\)](#)
- [Description page \(p.201\)](#)
- [Modular distribution blocks](#)

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.