



RoadFlair Gen2

BRP493 LED335/WW 250W 220-240V DM GM

RoadFlair Gen2, 33500 lm, 250 W, 730 warm white, Analog, Safety class I

RoadFlair Gen2 is brand new design road lighting product family, set to meet customers' all-round requirements, including high lumen efficacy for energy saving and sustainability, aesthetic design for nice shape and appearance, quality material and components for product reliability and long lifetime, professional optics for various applications fulfillment, dimming and system control interface for improving municipal operations and offering future-proof features. RoadFlair Gen2 competitive price would help on the acceleration of road lighting LED transformation, to a more sustainable society and smarter city.

Product data

General Information		Power Consumption	250 W
		Power Factor (Fraction)	0.95
Driver included	Yes	Connection	Screw connection block 3-pole
CE mark	CE mark	Cable	-
Light Technical		Temperature	
Luminous Flux	33,500 lm	Ambient temperature range	-40 to +50 °C
Correlated Color Temperature (Nom)	3000 K		
Luminous Efficacy (rated) (Nom)	133 lm/W		
Color rendering index (CRI)	>70	Controls and Dimming	
Light source color	730 warm white		
Optical cover type	Polycarbonate micro lens optic	Dimmable	Yes
		Control interface	Analog
Operating and Electrical			
		Mechanical and Housing	3
Input Voltage	220 to 240 V		
Line Frequency	50 or 60 Hz	Housing Material	Aluminium pressure die cast

|--|

Datasheet, 2023, December 13 data subject to change

RoadFlair Gen2

Housing Color	Aluminum and gray
Overall length	519 mm
Overall width	297 mm
Overall height	136 mm
Dimensions (Height x Width x Depth)	136 x 297 x 519 mm
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]


roduct Data	
der product name	BRP493 LED335/WW 250W 220-240V DM GM
Ill product name	BRP493 LED335/WW 250W 220-240V DM GM
full product code	872016972832500
un product code	8/20103/2832300
Order code	911401674906
Material Nr. (12NC)	911401674906
(====,	
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169728325
Numerator - Packs per outer box	1
EAN/UPC - Case	8720169728325

Initial Performance (IEC Compliant) Luminous flux tolerance +/-10% Power consumption tolerance +/-10%

Safety class I

Dimensional drawing

Protection class IEC



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, December 13 - data subject to change